

500 Series**COMBINATION pH or ORP SENSORS****Standard Features**

- Inexpensive
- 10 ft (3.3m) cable length
- Flow thru or submersion
- Industrial strength
- Tinned wire leads
- Single junction
- 1 year limited warranty

Application**ADD**

pH		P
ORP		R

Body Type

CPVC body, 1" MNPT threaded ends		575
Epoxy body, variable insertion - includes 3/4" CPVC compression ftg		585

Added Features (add only if required)

Automatic temperature compensation (pH only)		K
MBNC connector		BNC

Temperature Compensation (add only if temp. compensation is required)

GLI Temperature compensation device, PT1000 RTD		1
AquaMetrix Temperature compensation device, 300Ω thermistor		2

LAB STYLE ELECTRODES

P565	pH electrode, 30" cable with MBNC	
P565L	pH electrode, 10 ft (3.3m) cable with MBNC	
R565	ORP electrode, 30" cable with MBNC	
R565L	ORP electrode, 10 ft (3.3m) cable with MBNC	

ACCESSORIES & MOUNTING HARDWARE

MH575S	Submersion hardware/tank mounting for -575 body	
C35-3	3/4" MNPT CPVC compression fitting	
101-A	Preamplifier for 500 series probes	
101-A-BNC	Preamplifier for 500 series probes, w/ FBNC	
C42-5P-XXX	Interconnect extension cable, used with preamp [XXX=#ft example-050 = 50 ft] price/ft	
PROTECTOR-5	Electrode protector for 575 body type	
C42-43BNCF	BNC pigtail probe connector	