





Universal UltraPure KRYSTLE-CLEAR Gasket

For use with non-metallic Metric piping (PVDF, polypropylene, etc.) IR Butt-Weld and Socket Fusion Type Flange Adapter.

Bolt holes in accordance with ANSI B16.5 class 150 pattern.

Pipe Size inch	mm	Part #	I.D. inch J	O.D. inch K	L inch	Thickness inch	Bolt Circle Diameter	Bolt Hole #	Bolt Hole Diameter
1/2	20	KC-GK8.101	0.638	1.730	1.339	.100	2.375	4	5/8
3/4	25	KC-GK8.102	0.835	2.130	1.614	.100	2.750	4	5/8
1	32	KC-GK8.103	1.189	2.480	1.969	.100	3.125	4	5/8
1 1/4	40	KC-GK8.104	1.386	2.870	2.402	.100	3.500	4	5/8
1 1/2	50	KC-GK8.105	1.732	3.230	2.874	.100	3.875	4	5/8
2	63	KC-GK8.106	2.244	4.020	3.543	.100	4.750	4	3/4
2 1/2	75	KC-GK8.107	2.670	4.760	4.173	.100	5.500	4	3/4
3	90	KC-GK8.108	3.205	5.240	4.921	.100	6.000	4	3/4
4	110	KC-GK8.110	3.913	6.220	5.906	.100	7.500	8	3/4



Universal UltraPure KRYSTLE-CLEAR Gasket

For use with non-metallic Metric piping (PVDF, polypropylene, etc.) IR Butt-Weld and Socket Fusion Type Flange Adapter.

Bolt holes in accordance with ANSI B16.5 class 150 pattern.

Pipe Size inch	mm	Part #	I.D. inch J	O.D. inch K	Thickness inch	Bolt Circle Diameter	Bolt Hole #	Bolt Hole Diameter
6	160	KC-GK8.212	5.913	8.350	.100	9.500	8	7/8
8	200	KC-GK8.213	7.386	10.550	.100	11.750	8	7/8
9	225	KC-GK8.214	8.307	10.550	.100	11.750	8	7/8
10	250	KC-GK8.215	9.234	13.250	.100	14.250	12	1
12	315	KC-GK8.216	12.750	16.125	.100	17.000	12	1
14	355	KC-GK8.217	14.000	17.750	.100	18.750	12	1.125
16	400	KC-GK8.218	16.000	20.250	.100	21.250	16	1.125
18	450	KC-GK8.219	18.000	20.675	.100	22.750	16	1.25
20	500	KC-GK8.220	20.000	23.875	.100	25.000	20	1.25

Our gaskets are covered under US Patent #5,362,115 and Others Pending.

SAMPLE SPECIFICATION

Patented KC Multi-Ring® low torque design UltraPure KRYSTLE-CLEAR (elastomeric) gasket, KC Multi-Ring Products, Inc., sole source. To ensure proper laminar flow, geometrically align gasket and flange faces. Install using zinc-plated fasteners, no thread lubricants. Tighten fasteners in a star pattern, using progressive 4-pass tightening, to proper torque values.

Contact KC Multi-Ring Products, Inc. for sizes and materials not listed.